

# subwoofer series



Cuando la aplicación requiere un refuerzo de las bajas frecuencias los sistemas de subgraves de D.A.S. ofrecen la solución adecuada. Una variedad de versiones permite múltiples configuraciones con o sin la necesidad de añadir amplificadores adicionales. Son ideales tanto en instalaciones fijas, tales como clubes, discos y bares, como en aplicaciones móviles.

When the application requires increased bass response, the D.A.S. *subwoofer* systems are the answer. The models allow for multiple configurations, with or without the need for extra amplifiers. Ideal for music applications such as clubs, discos and bars, they are equally capable in portable applications such as mobile DJ's or general sound reinforcement.

MODEL	<i>sub-18G</i>	<i>sub-218G</i>
RMS Power Handling <sup>(1)</sup>	700 W	1400 W
Frequency Range (-10 dB)	35 Hz-160 Hz	27 Hz-160 Hz
Nominal Impedance	8 ohms	4 ohms
On-axis Sensitivity 1 W / 1 m	98 dB SPL	101 dB SPL
Rated Maximum Peak SPL at 1 m <sup>(1)</sup>	132 dB	138 dB
Bi-amp Recommended	100 Hz	100 Hz
Transducer/Replacement Parts	18G/GM 18G	2 x 18G/GM 18G
Connectors	2 x NL4 Speakon	2 x NL4 Speakon
Enclosure Material	Plywood	Plywood
Color/Finish	Black Paint	Black Paint
Dimensions (H x W x D)	63 x 54 x 65 cm 24.8 x 21.3 x 25.6 in	110 x 55 x 48.5 cm 43.3 x 21.7 x 19.1 in
Weight	38.4 kg (84.6 lb)	60 kg (132 lb)
Accessories	KITW100 TRD-5 FUN-AVANT 18A	ANL-2

Notes: 1. Based on a 2 hour test continuously applying 6 dB crest factor pink noise (IEC shaped).

2. Maximum calculated Peak SPL based on sensitivity and RMS power handling.

3. Maximum calculated Peak SPL based on sensitivity and RMS amplifier power.



sub-18G

- Sistema subgraves bass-reflex
- Altavoz de 18" para bajas frecuencias con bobina de 4"
- Diseño del recinto ofrece bajos con pegada
- Base con rosca para soporte

- Bass-reflex subwoofer system
- 18" low frequency transducer with 4" voice coil
- Enclosure design provides tight, punchy bass
- Top located threaded pole mount socket



sub-218G

- Sistema subgraves de alto rendimiento
- Dos altavoces de alta potencia 18G con bobinas de 4"
- 12 puntos de suspensión M10
- Pintura alta resistencia Isoflex
- Dos ruedas posteriores facilitan el transporte

- High output bass-reflex subwoofer system
- Twin 18G Hi-power woofers with 4" voice coil
- 12 M10 rigging points
- Painted in durable Isoflex paint
- Rear located wheels for ease of transport

